







234 SERIES WASHDOWN & CORROSION-RESISTANT UNIT HEATERS

The perfect solution for wet and corrosive non-hazardous heating applications. Wall, pole and ceiling mounting options. Ratings from 2 to 47kW and up to 600-volts three phase.



238 SERIES INDUSTRIAL UNIT HEATERS

Designed for maximum heating performance in non-hazardous and non-corrosive environments. Round design of the industrial unit heater provides uniform airflow over the elements preventing hot spots and ensure even discharge temperatures.



BTUR 240 SERIES COMMERCIAL UNIT HEATERS

Available in 50 standard models with ratings up to 50 kW at voltages of 208, 240, 277, and 480 single or three-phase. They are available with a wide variety of factory built-in or field-installed options.



BASEBOARD HEATERS

Designed to fit under large windows to prevent cold down drafts. These heaters can provide total or supplemental heating for a variety of applications.



WALL & CEILING HEATERS

Ten different wall and ceiling models to choose from, designed for commercial applications requiring higher kW's and quick heat up. Ratings range from 500 to 12,000 watts and up to 600 CFM to provide uniform temperatures for almost any application.



OTHER FORCED-AIR HEATERS

Cabinet unit heaters offer a unique combination of quality, efficiency, reliability and flexibility. Four sizes with ratings from 2,000 to 24,000 watts and voltages up to 480-volts. Wall or ceiling with surface, semi-recessed and recessed mounting options.







OPEN COIL DUCT HEATERS

Brasch has developed a standard quick ship line of HUA slip-in and HUP flanged open coil duct heaters to satisfy most space heating requirements. Control options include on-off, multi-stage and SCR proportional. Designed to provide flexible solutions for most reheat applications.



For use in industrial applications where dust or moisture may be present. Rugged Stainless Steel finned tubular elements are well suited for industrial applications to heat 100% outside air or for unfiltered air. Wide range of sizes, kW's and control options including proportional SCR control. Built tough for tough applications.



HEATERS FOR AIR HANDLERS AND VARIABLE AIR VOLUME (VAV) UNITS

UR approved for use in OEM air handling applications from VAV boxes to large indoor or outdoor air handling units. Brasch has the experience and heating products to custom tailor a heater for your application no matter how tough it is.







Designed to provide safe heating with a compact design in hazardous locations. CSA and FM approved for Classes I and II, Divisions 1 and 2, Groups B,C,D,E,F and G with temperature codes as low as T3C, 320°F (160°C). Optional controls with built-on thermostats. 0.5 to 9.5kW up to 600-volts three phase.



EXPLOSION-PROOF DUCT HEATERS

Brasch explosion-proof 227 Series and 220 Series duct heaters are Factory Mutual (FM) and CSA Approved. The 227 Series duct heater has the only standard product offering and features the industry's lowest ignition temperature code rating, T3C, 320°F (160°C).



233 SERIES EXPLOSION-PROOF UNIT HEATER

With the industry's lowest ignition temperature code rating, T3C, 320°F (160°C), the Ultra-Safe™ is designed for both safety and versatility.

We have the experience and expertise to provide you with the personalized support to arrive at customized solutions.

Email sales@Braschmfg.com or call 1-888-731-7010 to find your nearest Brasch representative.

